




VpCI™ ADDITIVES FOR FORMULATORS

BioClean 612



Bio Dipslide results during treatment with BioClean 612

TYPICAL APPLICATION

BioClean 612 is designed to offer bio-dispersing and preservative properties to water treatment applications susceptible to microbiological contamination.

APPLICATION CONSIDERATIONS

BioClean 612 functions well in the following water-based product characteristics:

pH 5.0 to 12.0
Avoid Temperature > 175°F

BioClean 612 should be added at, or near, the beginning of the production process with sufficient agitation.

For the correct dose, please review the product label and seek the assistance of a Cortec representative.

PRODUCT DESCRIPTION

BioClean 612 is a powerful aliphatic amide based organic penetrating agent and organic deposit dispersant for use in industrial applications. BioClean 612 also prevents the development of micro-organism protective layers and deposits. This dispersion and deposit prevention additive improves system cleanliness. When used with micro-biocides, greater control of micro-organisms can be achieved.

PHYSICAL PROPERTIES

- Actives: 15 %
- Density: 8.31 pounds per gallon
- pH (25°C, neat): 6
- Appearance: Clear to hazy, faint amber
- Miscible in water at high proportions
- Ionic Nature: Non-ionic
- Freeze Point: 1.67°C (35°F)
- Boiling Point: 100°C (212°F)

PACKAGING & STORAGE

BioClean 612 is available in 5 gal pails (19 L) and 55 gal drums (208 L). Store BioClean 612 in the closed container that it was shipped in. Store at temperatures between 7 and 26°C (50 - 80°F). The shelf life for this product is greater than 1 year.



FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR MORE
INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.


BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer
Revised 2/12/07. Cortec Corporation 2007. All rights reserved. Supersedes: none.
© 2007, Cortec Corporation. All Rights Reserved. Copying of these materials in any form
without the written authorization of Cortec Corporation is strictly prohibited.